



**NOTES**

1. STRAP MUST BE EQUIPPED WITH A SNAP HOOK OR A CHAIN ANCHOR ASSEMBLY AT THE END. IF STRAP IS EQUIPPED WITH A CHAIN ANCHOR ASSEMBLY THE HOOK MUST BE ZIP-TIED TO THE CHAIN PER AAR OPEN TOP LOADING RULES.
2. USE CORNER PROTECTORS WHERE NECESSARY TO PREVENT STRAPPING FROM CUTTING INTO BALES

DESCRIPTION/BLANK SIZE	MATERIAL	QTY.	PART NUMBER
5 STRAP/RATCHET ASSEMBLY - 4" WEBBING X 82' LONG	SEE NOTE 1	8	GB19-02-5
4 STRAP/RATCHET ASSEMBLY - 4" WEBBING X 41' LONG	SEE NOTE 1	30	GB19-02-4
3 D-RING ASSY. F654-1 & F654-2	PECK & HALE	60	GB19-02-3
2 TIE DOWN	A36	4	GB19-02-2
1 TIE DOWN	A36	12	GB19-02-1

**ASSEMBLIES**

**COPYRIGHT 2006 TRANSPORTATION TECHNOLOGY SERVICES, INC.**

DRAWN: TCK	<p><b>Transportation Technology Services</b> 1723 E Southlake Blvd, Ste 200 Southlake, TX 76092</p>	<p><b>GREENBRIER HAY HAULER</b> <b>TIE DOWN ARRANGEMENT</b></p>
DATE: 3-17-07		
CHECKED:		
DATE:	TOLERANCES:	SCALE: 1=24
	UNLESS NOTED:	NEXT ASSEMBLY NO.
	DIMS: ± 1/8"	DRAWING NO.
	ANGLES: ± 1°	GB19-02
	HOLE Ø: ± 1/32"	SHT.
		1/1